



## Model TA-2102 *smarter* Diborane B<sub>2</sub>H<sub>6</sub> Gas Detector

### ➤ Features

- no false alarms** electrochemical sensor technology
- Self-Calibration adjusts monthly based on sensor life curve
- Auto-Gas Calibration, non-intrusive, hands-free, magnetic switches
- Not affected by temperature -20°C to +40°C, stable by design
- LCD display - 12 characters x 2 lines - provides user interface with magnetic switches - no dip switches - LED indicators
- Offsite sensor calibration with memory chip embedded in sensor
- Peak Value, 15-min. TWA, Remaining Sensor Life, Replace Sensor indication and number of days since last gas calibration
- Loop Powered - Intrinsically Safe option
- Optional enclosures - 316 stainless steel, Nema 4x polycarbonate
- Available suitable for use in **SIL 2** environments / Advanced diagnostics

Part No. 01-2241

#### Options

- Sensor Cable
- Sample Pump
- Duct Mount Kit
- Dust Guard
- Splash Guard
- Wireless Module
- 110/220 VAC
- Calibration Kits
- 316 SS Enclosure

### ➤ Specifications

Detection Principle:	Electrochemical - Amperometric
Detection Method:	Diffusion or Sample Drawing
Detection Range:	0.00 - 1.00 ppm (parts-per-million)
Calibration Method:	Non-intrusive, magnetic tool
Operating Voltage:	10 - 30 VDC, 24 VDC nominal
Power Requirements:	0.48 W @ 24 VDC
Electrical Connections:	Power (24 VDC) and Signal (4-20mA)
Cable Requirements:	2-wires, shielded
Connection Type:	2-wire, loop powered
Resolution:	0.01 ppm minimum detection level
Zero Drift:	less than 0.02 ppm
Temperature Range:	-20°C to +40°C
Humidity Range:	15 - 95% RH, non-condensing
Response Time:	<30 sec. to 90% of final reading
Recovery Time:	<30 sec. to 90% recovery
Sensor Service Life:	>2 years typical; normal conditions
Electronic Enclosure:	Ex-Proof, aluminum or 316 SS
Enclosure Certifications:	CSA/UL/FM Class I GR B,C,D

### ➤ Applications

- Semiconductors
- Chemical Processing
- Laboratories
- More

Specifications subject to change without notice due to continued program of product innovation.

Toxic • LEL Combustible • Oxygen • VOCs • Hydrides • Hydrocarbons  
Gas Detection **no false alarms** Fire Detection

Tel: 510-656-2001 • Fax: 510-656-2004 • Email: sls@mil-ram.com • Fremont, CA