

MIL-RAM TECHNOLOGY

no false alarms

Since 1990

ISO 9001:2008 Registered

Tel: 510-656-2001 • Toll-Free: 888-464-5726 • Email: sls@mil-ram.com • Web: mil-ram.com



Model TA-2100 *smarter* Methyl Bromide Gas Detector

➤ Features

- no false alarms** PID Photo-Ionization sensor technology
- Self-Calibration adjusts monthly based on sensor life curve
- Auto-Gas Calibration, non-intrusive, hands-free, magnetic switches
- Not affected by temperature -40°C to +55°C, stable by design
- LCD display - 12 characters x 2 lines - provides user interface with magnetic switches - no dip switches - LED alarm indicators
- Offsite sensor calibration with memory chip embedded in sensor
- Peak Value, 15-min. TWA, Remaining Sensor Life, Replace Sensor indication and number of days since last gas calibration
- Optional Relay Module; low, mid, high and fault conditions
- Optional RS-485 Modbus RTU Network interface
- Advanced diagnostics - continuous on-board systems monitoring

Part No. 01-26199

Options

- Modbus RTU
- Relay Module
- Sensor Cable
- Sample Pump
- Duct Mount Kit
- Dust Guard
- Splash Guard
- Wireless Module
- 110/220 VAC
- Calibration Kits
- 316 SS Enclosure

➤ Specifications

Detection Principle:	PID Photo-Ionization
Detection Method:	Diffusion or Sample Drawing
Detection Range:	0-400 ppm (parts-per-million)
Calibration Method:	Non-intrusive, magnetic tool
Operating Voltage:	12 - 30 VDC, 24 VDC nominal
Power Requirements:	1.82 W @ 24 VDC
Electrical Connections:	Power (24 VDC) and Signal (4-20mA)
Cable Requirements:	3 or 4 wires, shielded
Optional Connections:	RS-485 Half-duplex (Modbus RTU)
Resolution:	1 ppm minimum detection level
Zero Drift:	less than 1% of full-scale
Temperature Range:	-40°C to +55°C
Humidity Range:	0 - 99%RH, non-condensing
Response Time:	<30 sec. to 90% of final reading
Recovery Time:	<30 sec. to 90% recovery
Lamp Service Life:	18 mos. typical; depends on conditions
Electronic Enclosure:	Ex-Proof, alum. or 316 SS, Nema 4x
Certifications:	UL, Class I, Division 1, GR B,C,D

➤ Applications

- Pesticide
- Fungicide
- Fumigation
- Agriculture
- Chemical Processing
- Laboratories
- More

Toxic • LEL Combustible • Oxygen • VOCs • Hydrides • Hydrocarbons

Gas Detection

no false alarms

Fire Detection

Specifications subject to change without notice due to continued program of product innovation.

Tel: 510-656-2001

Fax: 510-656-2004

Email: sls@mil-ram.com

Fremont, CA