

MIL-RAM TECHNOLOGY

Since 1990

Gas Detection Controller

Digital Modbus RTU *smarter* Transmitter Network

Gases & Instrumentation
2010 Golden Gas Award

TA-2016MB-WM Controller Features

- ◆ Use with any Mil-Ram Model TA-2100MB *smarter* Transmitter. Toxic/LEL/VOC/Oxygen: hundreds of different gases and vapors.
- ◆ 16-Channel system utilizing RS-485 Modbus RTU Network.
- ◆ Multi-drop Network eliminates separate wiring to each Transmitter.
- ◆ Four relays (SPDT), 10 Amp. common to all channels. Select latching or non-latching function. Low, Mid, High and Fault relays. LED alarm indicators. Audible buzzer alarm. External alarm stations optional.
- ◆ *Optional*: Remote Relay Modules, Modbus enabled, can be installed at any point on RS-485 network. Up to 16 modules per network. Up to 16 different zones. Conveniently install relays at point of use. Eliminates long wiring runs between relays and field installed alarms.
- ◆ *Optional*: Remote Analog Output Module. Provides discrete analog 4-20mA output (16 bit resolution) per channel.
- ◆ *Optional*: Remote Digital Output Module. Provides RS-485 Modbus RTU interface to Centralized System (e.g. PLC)
- ◆ *Optional*: Analog Input Module to connect standard 4-20mA Transmitters where traditional analog installation is preferred.
- ◆ Backlit 16 characters x 2 lines LCD display. Auto-scrolls to provide channel data and fault conditions. Indicates alarm status.
- ◆ Simple front panel, push button channel setup. Auto-Configuration wizard provides rapid channel setup without special knowledge.
- ◆ Nema 4x weather-proof polycarbonate enclosure (XP available)
- ◆ Continuous Diagnostics. *Wireless* Options (consult factory).

Sensors *patented* by Mil-Ram

- ◆ *no false alarms* Mil-Ram electrochemical sensor technology
- ◆ No *zero drift* with changes in temperature/humidity/pressure
- ◆ No LEL, methane, hydrocarbons, CO, CO₂, VOCs gas interference
- ◆ Do not saturate with occasional exposure to high gas levels
- ◆ Do not *go to sleep* after long periods in gas-free air
- ◆ Chemically selective based on unique electrolyte chemistry
- ◆ Long life: >3 years typical under normal operating conditions

Digital Modbus
16-Channel Control System
(8 Channel Model Available)



Model TA-2016MB-WM
Auto-Configuration
110 VAC or 24 VDC

16 Channel System
Modbus RTU Network
-up to 16 Gas Detectors
-up to 16 Relay Modules
-up to 16 Alarm Zones



RS-485 Modbus RTU Network



Relay Module

(Analog Input Module available for connecting traditional 4-20mA Transmitters)

Gas

Detectors



Model TA-2100MB *smarter* Transmitters
(LEL, Toxic, VOC, Infrared, MOS, more)



MIL-RAM TECHNOLOGY, INC.
REGISTERED TO ISO 9001:2008
FILE NUMBER 10000574 QM08

MIL-RAM
Patented Technology
no false alarms
Gas Detection Systems
ISO 9001:2008 Registered

Tel: 510-656-2001 • Toll Free: 1-888-4MILRAM (1-888-464-5726)
Fax: 510-656-2004 • Email: sls@mil-ram.com • Web: www.mil-ram.com