

MIL - R A M T E C H N O L O G Y

no false alarms

Gas Detection Systems

**New &
smarter**

**SiH₄
Silane**

FEATURES: 3 or 4-Wire

3 or 4-Wire *smarter* Transmitter

- ***no false alarms*** - does not react with changes in temperature/humidity/pressure
- **Does Not Drift** - no autozeroing or adjustments required
- **Rapid Warm-up** - ready to calibrate 3 minutes after power applied - does not require bias voltage to stay ready - no need to wait hours for stabilization
- **Not Affected by Humidity** - 10% to 95% relative humidity - continuous
0% to 99% relative humidity - intermittent
- **Not Affected by Temperature** - -20° C to +40° C is not temperature compensated
- **Self-Calibration** - microcontroller electronics automatically adjusts span calibration over time based on typical life curve for sensor - sensors not routinely calibrated stay much closer to proper calibration - reduces calibration frequency - actual field calibration data re-adjusts life curve
- **Sensor Life Remaining** - determined based on sensor life curve, calibration history and electrical characteristics of sensor - shown on LCD display
- **Non-Intrusive One-Man Calibration** - use magnet to actuate zero and span calibration switches behind enclosure glass window - no manual adjustments required - no need to open enclosure
- **Off-site Sensor Calibration** - calibrate sensor in lab and install on any same type *smarter* Transmitter with no further calibration required - calibration data automatically uploads to transmitter to ensure precise calibration
- **Alarm Settings** - user adjustable low, mid and high alarm settings
- **Alarm Relays** - (option) low, mid and high relays, user selectable non-latching/latching, non-energized/energized - fault relay, non-latching, normally energized - all relays rated 20 amps
- **Peak Value** - 15 min. TWA/No. days since last gas calibrated
- **Loop Test** - transmitter outputs 4/8/12/16/20mA signal to verify readings and alarms at controller electronics
- **Diagnostics** - continuous analysis of transmitter system to report any fault conditions, e.g. low sensor life, low gas sensitivity, sensor disconnected, etc.
- **Maintenance Free** - no replenishment of electrolyte or water during 2+ years of normal life
- **Long Life** - over 2 years continuous operation
- **Fast Response** - 90% of reading in less than 30 seconds
- **Fast Recovery** - 90% recovery in less than 30 seconds
- **Not Saturated** by occasional high concentrations of gas in the work environment (continuous gas exposure reduces service life)
- **Stays Awake** - does not go to sleep when gas is absent for long periods of time
- **Chemically Selective**

Self-Calibration = Cost Reduction



2 line x 12 Character Back-lit LCD Display

Modbus Option—RS-485 Modbus RTU, Ethernet Modbus TCP/IP. Link up to 247 *smarter* Transmitters on a twisted pair cable and collect data continuously at host computer, PLC, PC, data-logger, etc. P/N: 01-2546SMTRMB

TRANSMITTER SPECIFICATIONS:

Operating Voltage: 12 or 15-30VDC
Transmitter Outputs: 4-20 mA, RS-485 Modbus RTU (option)
Sampling Method: Diffusion (Sample-Draw Available)
Calibration Method: Non-Intrusive, magnetic switches
Enclosure: CSA/FM/UL/CENELEC/KEMA
Class I, Div. I, Groups B/C/D
Class II, Groups E/F/G
Class III, Type 4X
Weight: 3.5lbs/1.589kg.
Part Number: 01-2546SMTR
Power Required: 1.08W at 24VDC/2.60W Max. w/Relays

Note: Specifications subject to change without notice

SENSORS:

Detection Principle: Electrochemical
Detection Method: Diffusion (Sample-Draw Available, Nema 4X)
Detection Range: 0.0-50.0 ppm; 0.0-100.0 ppm
Output Signal: Linear
Resolution: .01 ppm
Response Time: <30 sec. to 90% of final reading
Recovery Time: <30 sec. to 90% recovery
Humidity Range: 10% - 95% RH, non-condensing - continuous
0% - 99% RH, non-condensing - intermittent
Temperature Range: -20°C to +40°C
-4°F to +104°F
Pressure Range: Atmospheric \pm 15%
Zero Drift: <.02 ppm
Position Sensitivity: None
Storage Life: >6 months in container
Life Expectancy: >2 years in clean air


Patented Technology
no false alarms
Gas Detection Systems
ISO 9001:2000 Certified

Toll Free: 888-4MILRAM • 1-888-464-5726

4135 Business Center Drive • Fremont, CA 94538

Phone: 510-656-2001 • Fax: 510-656-2004

sls@mil-ram.com • www.mil-ram.com

www.wirelessmil-ram.com