

MIL - RAM TECHNOLOGY

no false alarms

Gas Detection Systems

**New &
Smarter
2-Wire**

**O₂
Oxygen**

FEATURES: **2-Wire**

2-Wire *smarter* Transmitter

Self-Calibration = Cost Reduction

- **no false alarms** - does not react with changes in temperature/humidity/pressure
- **Does Not Drift** - no autozeroing or adjustments required
- **Rapid Warm-up** - ready to calibrate 3 minutes after power applied - does not require bias voltage to stay ready - no need to wait hours for stabilization
- **Not Affected by Humidity** - 15% to 90% relative humidity - continuous
0% to 99% relative humidity - intermittent
- **Not Affected by Temperature** - -15° C to +40° C is not temperature compensated
- **Self-Calibration** - microcontroller electronics automatically adjusts span calibration over time based on typical life curve for sensor - sensors not routinely calibrated stay much closer to proper calibration - reduces calibration frequency - actual field calibration data re-adjusts life curve
- **Sensor Life Remaining** - determined based on sensor life curve, calibration history and electrical characteristics of sensor - shown on LCD display
- **Non-Intrusive One-Man Calibration** - use magnet to actuate zero and span calibration switches behind enclosure glass window - no manual adjustments required - no need to open enclosure
- **Off-site Sensor Calibration** - calibrate sensor in lab and install on any same type **smarter** Transmitter with no further calibration required - calibration data automatically uploads to transmitter to ensure precise calibration
- **Peak Value** - 15 min. TWA/No. days since last gas calibrated
- **Diagnostics** - continuous analysis of transmitter system to report any fault conditions, including replace sensor and sensor disconnected
- **Loop Test** - transmitter outputs 4/8/12/16/20mA signal to verify readings and alarms at controller electronics
- **Maintenance Free** - no replenishment of electrolyte or water during 2+ years of normal life
- **Long Life** - over 2 years continuous operation
- **Fast Response** - 90% of reading in less than 30 seconds
- **Fast Recovery** - 90% recovery in less than 30 seconds
- **Not Saturated** by occasional high concentrations of gas in the work environment
- **Stays Awake** - does not go to sleep when gas is absent for long periods of time
- **Chemically Selective**

SENSORS:

| | |
|------------------------------|---|
| Detection Principle: | Electrochemical |
| Detection Method: | Diffusion (Sample-Draw Available, Nema 4X) |
| Detection Range: | 0.0-25.0% |
| Output Signal: | Linear |
| Resolution: | 0.1% |
| Response Time: | <30 sec. to 90% of final reading |
| Recovery Time: | <30 sec. to 90% recovery |
| Humidity Range: | 15% - 90% RH, non-condensing - continuous 0% - 99% RH, non-condensing - intermittent |
| Temperature Range: | -15°C to +40°C 5°F to +104°F |
| Pressure Range: | Atmospheric ±15% |
| Position Sensitivity: | None |
| Storage Life: | 6 months in container |
| Life Expectancy: | >2 years in clean air |



TRANSMITTER SPECIFICATIONS:

| | |
|----------------------------|---|
| Operating Voltage: | 10-30VDC, 2-Wire Loop Powered |
| Transmitter Output: | 4-20 mA |
| Sampling Method: | Diffusion (Sample-Draw Available) |
| Calibration Method: | Non-Intrusive, magnetic switches |
| Enclosure: | CSA/FM/UL/CENELEC/KEMA Class I, Div. I, Groups B/C/D Class II, Groups E/F/G Class III, Type 4X |
| Weight: | 3.5lbs/1.589kg. |
| Part No.: | 01-2225SMTR |

Note: Specifications subject to change without notice

Toll Free: 888-4MILRAM • 1-888-464-5726

4135 Business Center Drive • Fremont, CA 94538

Tel: 510-656-2001 • Fax: 510-656-2004

sls@mil-ram.com • www.mil-ram.com

www.wirelessmil-ram.com

MIL-RAM
Patented Technology
no false alarms
Gas Detection Systems
ISO 9001:2000 Certified